

ROOF PATCH

PLASTIC ROOF CEMENT

1. PRODUCT NAME:

Roof Patch Plastic Roof Cement

2. MANUFACTURER:

GEOCEL, LLC
P.O. Box 398
Elkhart, IN 46515 USA
Phone: (800) 348-7615
Fax: (800) 348-7009
www.GeocelUSA.com

3. PRODUCT DESCRIPTION:

Roof Patch Plastic Roof Cement is a single-component, asphalt-based cement designed to bond on wet or dry surfaces for many construction, roofing, agricultural, manufacturing, and industrial applications.

Product Benefits:

- Use on wet or dry surfaces, even underwater
- Formulated to seal quickly; will not pull apart or lose its bond
- Remains soft and pliable, and resists temperature change

Basic Uses:

- Ideal for patching and roof maintenance, sealing and repairing shingles, flashings, and roof seams
- Seals vents, pipes, chimneys, and gutters
- Seals metal building seams
- Shingle tab cement

Adheres To: Asphalt, modified bitumen, and other common building substrates



Composition and Materials:

Roof Patch Cement is an asphalt-based material containing no asbestos. This formula produces a product that will bond on wet or dry surfaces.

Grade: Gun grade consistency

Primer: Not required on most surfaces

Packaging: 10 fl. oz. cartridge

Colors: Black

Limitations:

- Do not paint or thin
- Do not use with single-ply membranes such as EPDM, PVC, CSPE, etc.
- Product contains solvents that may craze some plastic materials
- Store at room temperature for 24 hours before use to improve ease of application

4. INSTALLATION:

Surface Preparation: For best results, remove dust and dirt with a stiff brush or broom. Remove old sealant or roof coatings. Surface to be repaired must be clean.

Cure: 1 to 3 days

Service Temperature: -40° F to 150° F (-40° C to 66° C)

Application Temperature: 0 F° to 140° F (-18° C to 60° C)

Application and Tooling: Apply with standard caulking gun over area to be sealed. If tooling is

desired, use a trowel or putty knife, occasionally dipping in paint thinner. When application is to take place at temperatures below 50° F (10° C), store Roof Patch Cement at room temperature for 24 hours prior to use in order to make application easier.

Cleaning: Clean tools with paint thinner or mineral spirits. Observe manufacturer's precautions when using toxic or flammable solvents.

Storage Life: One year (unopened cartridge)

Warning: Harmful or fatal if swallowed. If swallowed, call a physician immediately. May be harmful if inhaled in an enclosed space. Use only in a well-ventilated area. Avoid prolonged skin contact. Combustible (during cure). **KEEP OUT OF REACH OF**

5. AVAILABILITY AND COST:

Marketed throughout the U.S., Canada, and in select foreign markets, it is available from lumber yards, hardware stores, and home centers. Cost and further technical data are available from your local Geocel representative or from Geocel's corporate offices.

Note: Product produced after Dec. 31, 2010 may not be sold in the state of California.

6. LIMITED WARRANTY:

Geocel, LLC warrants that the product is manufactured according to their published standards. The company guarantees for 5 years from the date of manufacture that Roof Patch Cement will not crack due to normal expansion and contraction and that it will not lose its adhesion or cohesion. Geocel, LLC will, at its option, either refund the purchase price of, or provide replacement for, that portion of Roof Patch Cement which fails to perform in accordance with this warranty. Such refund or replacement will constitute the limit of Geocel's liability and obligation for any such failure. Geocel, LLC will not be liable or obligated otherwise for any loss or damage arising directly or indirectly from this product, or the use or failure thereof, whether based on breach of warranty or negligence.

7. MAINTENANCE:

No maintenance should be required. If the sealant is damaged, either remove bead and reseal, or apply additional Roof Patch Cement over the damaged area.

8. TECHNICAL SERVICES:

Geocel representatives throughout the U. S. are available to provide technical assistance. Geocel's in-house technical staff and laboratory facilities are equipped to respond to specific requests for further information and/or applications testing.

THEORETICAL YIELD per 10.0 fl. oz. cartridge

| Joint Size | Linear Feet |
|-------------|-------------|
| 1/4" x 1/4" | 24.1 |
| 1/4" x 3/8" | 16.0 |
| 1/4" x 1/2" | 12.0 |
| 1/2" x 3/8" | 8.4 |
| 1/2" x 1/2" | 6.0 |
| 3/4" x 1/2" | 4.0 |

For additional product information, refer to the product spec sheet located at www.GeocelUSA.com.