

## Geocel® RUST CONVERTER

**PRODUCT NAME:**

Geocel® Rust Converter

**MANUFACTURER:**

Geocel Products Group

A Business Unit of

The Sherwin-Williams Company

("Geocel Products Group")

Cleveland, OH 44115

Phone: (800) 348-7615

Fax: (800) 348-7009

www.GeocelUSA.com

**PRODUCT DESCRIPTION:**

Geocel® Rust Converter is a fast-drying primer that converts rust and provides a paintable surface. Geocel Rust Converter can be used on metal, steel, galvanized surfaces and more.

**PRODUCT BENEFITS:**

- Makes unsightly surfaces look new again
- Convert rust in one easy step
- Protects against further corrosion
- Sprays clear, rust turns black when ready to paint
- Dries in 2 to 3 hours

**RECOMMENDED USES:**

Use on metal, steel, galvanized surfaces, and more.

**SURFACE PREPARATION:**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log onto [www.epa.gov/lead](http://www.epa.gov/lead). Surface should be clean, dull & dry. Remove loose rust & paint with wire brush or sand paper.

**PAINTING CONDITIONS:** Spray outdoors or in a well-ventilated area. Protect surrounding areas. Best results when air and surface temperature are between 40-80°F. For best results, do not use in high humidity.



**APPLICATIONS:** Shake can prior to and during use. Hold can 8-12" from surface, spray in sweeping motion side to side with slight overlap. Apply multiple thin coats.

**COVERAGE:** 15 - 20 sq. ft.

**DRY TIME:** Dries to the touch in 2-3 hours. Recoat anytime. Allow 24 hours prior to painting.

**AFTER USE:** To prevent clogs, hold can upside down and spray until clear gas appears. To clean paint on actuator, wear eye protection and wipe off with lacquer thinner – DO NOT stick pin in opening. Recycle empty can per local regulations.

**CAUTIONS:** CONTAINS ETHYLENE GLYCOL MONOBUTYL ETHER AND KETONES. DANGER! EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. SEE SAFETY DATA SHEET.

**DANGER:** Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

**PERFORMANCE TESTING:**

Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is express or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse.

**LIMITED WARRANTY:** If when applied according to label directions this product fails to perform in accordance with its published literature, upon satisfactory evidence of product failure, and as your sole remedy, we will either replace the product at no cost or refund the original purchase price for that portion of product that fails to perform in accordance with this limited warranty. Labor or costs associated with labor are not included. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR

IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER AND SUCH DAMAGES ARE EXPRESSLY EXCLUDED. Some states do not allow the exclusion or limitation of incidental or consequential damages or how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This limited warranty gives you specific legal rights, and you may also have other rights which vary from state to state.